





Security and Control Panel

Built on the legacy of the groundbreaking GC2e security panel, the 2GIG GC Touch sets a new benchmark for simplicity in setup, ease of use, and performance – at a value oriented price point.

Customers will love the sleek new panel design, 7-inch touchscreen, intuitive and modern user interface, and dark mode option. 800 series Z-wave enables smart home automation for lights, locks, thermostats, garage doors, and more. The GC Touch is also optimized for Alarm.com Scenes.

GC Touch set up is more streamlined than ever and works with all 2GIG 345Mhz and compatible security sensors.



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.

Modern Panel Design

The GC Touch is easy to use with updated design, large 7" screen, and intuitive UI.



Live Video

See who is at the door or view surveillance cameras in real time.



Bluetooth Disarm

Streamlined system disarming without entering pin codes.





Discover more about the 2GIG GC Touch

2GIG-TOUCH-NA

Security and Control Panel





FEATURES

- 7" Capacitive touchscreen
- · Crystal clear 2-way voice
- · Bluetooth disarm
- Up to 128 Zones and 64 Users
- · Z-Wave 800 series
- · Simplified user interface
- Streamlined programming

Panel Features

Bluetooth disarm

Video live view on the panel

Alarm.com cameras on the panel

Doorbell on the panel with 2-way audio

Secure 4 or 6-digit personal codes

Security

345S sensors, 345MHz sensors, eSeries encrypted sensors

Emergency (fire, medical, police)

64 users

128 wireless zones

Keyfobs

Keypads

Audio

2-way voice

Front firing speaker

Siren/piezo

Annunciations and chimes

Smart Home Automation

Integrated Z-Wave 800 series

Create and execute scenes and schedules (with Alarm.com)

Voice Controls

Google Assistant

Amazon Echo

Siri Shortcuts

Communication

4G LTE (Verizon and AT&T)

Wi-Fi 2.4 GHz (802.11 b/g/n, WPA-TKIP/WPA2-AES)

Wi-Fi access point

Operating Specifications

Operating temperature: $32^{\circ}F$ to $104^{\circ}F$ ($0^{\circ}C$ to $40^{\circ}C$) Max humidity 90%

100-240VAC 50/60Hz 1.7A 14VDC adapter Lithium-polymer backup battery (24 hrs.)

Dimensions: 7.5 L x 6.0 W x 1.25 D (in)

19.05 L x 15.24 W x 3.175 D (cm)

Weight: 1.39 lbs | 0.63 kg

Certifications

FCC: Part 15

ISED, RSS210/RSS247

UL 985, UL 1023, UL 2017, ULC-S545, ULC S304

(for Canada)

SIA CP-01 2019

CSFM BML Listed

PROP-65, ROHS

Firmware Updates

Over-the-air, USB

Warranty

Limited 3 years





Specifications and availability subject to change without notice.

The **2GIG GC Touch** panel is a key element for residential and commercial properties to keep clients feeling secure. Pair with sleek, modern **2GIG 345S** sensors that seamlessly integrate into any environment and include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch**™ and **2GIG EDGE**™ security panels.





