



345S
SECURITY SENSOR

**Security Sensor with On/Off
Switchable Encryption.**



2GIG-RPT100-345

345MHz Repeater

The 2GIG® 345MHz Repeater enhances 2GIG security systems by offering greater flexibility in wireless sensor placement. It can be strategically positioned to extend the range of 2GIG panels, making it ideal for larger projects.

This device repeats both 2GIG and Honeywell sensor signals to 2GIG panels. As a plug-and-play unit, the Repeater begins signal repetition immediately upon powering on. In the event of an AC power outage, its rechargeable battery ensures continuous operation.



**Stock half as many SKUs
on trucks.**

Easily choose encrypted/
non-encrypted operation
with an internal switch.
2GIG 345S sensors work
for any installation.

**Complete 2GIG security
ecosystem.**

345S sensors work with
the all-new GC Touch,
revolutionary 2GIG EDGE,
and earlier security &
control panels from 2GIG.

GC TOUCH™
2GIG EDGE™



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.



**Discover more
about 2GIG
345S sensors**

2GIG-RPTR100-345

345MHz Repeater

345S
SECURITY SENSOR



FEATURES

- Repeats 2GIG and Honeywell signals on 345MHz frequency
- Repeats both encrypted and nonencrypted sensor signals out of the box
- On-off switchable supervisory encryption
- 24-hour backup battery included
- Repeat indicator in the signal eliminates “repeated signal storm”
- Optional zone programming to supervise Tamper, AC Loss, and Low Battery

TECHNICAL SPECIFICATIONS

Overall Size	102 X 76 X 46 mm (4.0" X 3.0" X 1.8")
Weight (without battery)	125 g (4.4 oz.)
Installation Type	Wall mounted
Operating Frequency	345 MHz
Operating Temperature Limits	-10° C to 55° C (14° F to 131 ° F)
Relative Humidity	5 to 85% non-condensing
Power Type	Remotely powered by AC adapter, with internal battery backup
AC Adapter Nominal Input Voltage	100–240 VAC 50/60 Hz
AC Adapter Nominal Output Voltage	14 VDC

Specification and availability subject to change without notice.

2GIG 345S sensors offer reliable security coverage for residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, 345S sensors include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch™** and **2GIG EDGE™** security panels.



2GIG.COM

 **2GIG.**
a Nice brand