




345S
SECURITY SENSOR

**Security Sensor with On/Off
Switchable Encryption.**

2GIG-FF100-345

FireFighter™ Smoke and CO Detector/Listener

The 2GIG® FireFighter is a quick and easy way to add smoke alarm monitoring to your 2GIG control panel. FireFighter is specifically tuned to recognize the specific cadence of a UL listed smoke or CO detector's alarm. This unique audio technology monitors existing UL listed smoke detectors in a home and will send a wireless signal to the control panel when an alarm is detected. The control panel will then contact the connected central monitoring station.



**Stock half as many SKUs
on trucks.**

Easily choose encrypted/
non-encrypted operation
with an internal switch.
2GIG 345S sensors work
for any installation.

**Complete 2GIG security
ecosystem.**

345S sensors work with
the all-new GC Touch,
revolutionary 2GIG EDGE,
and earlier security &
control panels from 2GIG.

GC TOUCH
2GIG EDGE™



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.



SCAN ME

**Discover more
about 2GIG
345S sensors**

2GIG-FF100-345

FireFighter™ Smoke and CO Detector Listener

345S
SECURITY SENSOR



FEATURES

- Monitors any existing UL listed smoke, CO, or combo detectors
- Does not impact UL or Fire Marshall approval of existing detectors
- Uses one CR123A long life lithium battery
- FCC, IC, and ETL listed in US and Canada to UL985 standard
- Default non-encrypted; encryption enabled via onboard switch

PACKAGE CONTENTS

- FireFighter Smoke and CO Detector Listener
- CR2032 battery
- Mounting package included

COMPATIBLE ALARM SYSTEMS

- 2GIG Panels

TECHNICAL SPECIFICATIONS

Wireless Protocol/Freq	2GIG345 MHz
Detection Distance	6 inches maximum
Transmitter Frequency	345 MHz (crystal controlled)
Supervisory Interval	64 minutes
Operating Temperature	32° - 120°F (0° - 49°C)
Relative Humidity	5-95% RH, non-condensing
Battery (included)	CR123 or equivalent Lithium battery
Backup Battery Life	5 years
Certification	FCC, IC, ETL in USA and Canada to UL 985 standard

Specification and availability subject to change without notice.

*This product has been tested and verified to operate with the above alarm panel systems. Other brand/model 345 MHz alarm systems may also work with this product.

2GIG 345S sensors offer reliable security coverage for residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, 345S sensors include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch™** and **2GIG EDGE™** security panels.



2GIG.COM

2GIG
a Nice brand