



345S
SECURITY SENSOR

**Security Sensor with On/Off
Switchable Encryption.**



2GIG-TILT100-345 Wireless Tilt Sensor

The 2GIG® TILT100-345 sensor is designed to monitor the tilt of assets like garage doors, mailboxes, pet doors, or storm cellar doors. It communicates with the control panel using a 345 MHz frequency, transmitting a signal when tilted beyond 45 degrees and sending a restore signal once it returns to a less than 45-degree angle. The sensor includes a tamper switch that alerts if the cover is removed and features low battery monitoring, sending a report when the battery level is low.

The sensor supports both non-encrypted (default) and encrypted mode, configurable via a switch.



**Stock half as many SKUs
on trucks.**

Easily choose encrypted or non-encrypted operation with an internal switch. 2GIG 345S sensors work on any installation.

**Complete 2GIG security
ecosystem.**

345S sensors work with the all-new GC Touch, revolutionary 2GIG EDGE, and earlier security & control panels from 2GIG.

GC TOUCH
2GIG EDGE™



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.



**Discover more
about 2GIG 345S
sensors**

2GIG-TILT100-345

Wireless Tilt Sensor

345S
SECURITY SENSOR



FEATURES

- Monitors tilt status
- Case tamper and battery supervision 2GIG 345MHz compatible
- Double-sided tape and mounting screws included
- Battery life up to 10 years
- On-off switchable encryption

TECHNICAL SPECIFICATIONS

Transmitter Frequency	345MHz
Compatibility	2GIG Panels
Code Outputs	Alarm; Alarm Restore; Supervisory; Tamper; Tamper Restore; Low Battery
Supervisory Interval	70 Minutes
External Input	Accepts NC or NO dry contact devices
Housing Material	ABS Plastic
Operating Temperature	2° to 120°F (-16 to 49°C)
Relative Humidity	15% to 85%, Non-condensing
Batteries (Installed)	One 3V CR2450 Lithium Battery
Battery Life	Up to 10-years
Certification	ETL, FCC, Industry Canada

Specification and availability subject to change without notice.

2GIG 345S sensors offer reliable security coverage for residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, 345S sensors include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch™** and **2GIG EDGE™** security panels.



2GIG.COM

 **2GIG**
a Nice brand